

**SPC Click Vinyl Tile Flooring (Grey Oak)
with Built in Underlay per Sq M- Click Vinyl
Tile Floors for Kitchen, Bathroom, Living
Room - LVT Rigid Core Stone Polymer
Composite Waterproof Click Tonge &
Groove Luxury Vinyl Tile Flooring Grey Oak**

£21.99

Product Description

1100mm x 184mm x 6mm per plank. 5 planks per box (covers 1 sq m per box). **Price is per sq metre. Sold by the square metre. 1 Sqm in each box. ie. 20sq m will be 20 boxes. Simply enter the number sq m of flooring you require in the quantity box.** We recommend ordering an extra 5-10% coverage to cover wastage / cuts as delivery charges may apply for single sq meterage orders if you are short.

Flooring & tile products are not sold per pack, they are sold by the square metre. Price is per sq metre. Sold by the square metre ie. Qty 20 added to cart is 20sq m will be 20 boxes of 1 sqm each. Enter the number of sq m required in the QTY box.

To order FREE Sample of this product, [click here](#)

SPC Click Vinyl Tile Flooring - Grey Oak c/w 1mm Underlay Layer - Rigid Core 5.2mm + 1mm underlay Layer - Stone Polymer Composite Waterproof Click Tonge & Groove Luxury Vinyl Tile Flooring - Grey Oak

Get that sought-after authentic wood flooring look without the cost and upkeep required of the real thing thanks to SPC Luxury Vinyl Tiles; a click system is easy-to-install by any professional or DIY'er, a vinyl tile that faithfully replicates natural timber

across a wide range domestic and commercial applications.

Key Features

- [AUTHENTIC TEXTURED WOODGRAIN EFFECT] Embossed Surface + Micro Bevel Edge make this flooring as authentic as engineered wood with a Matt finish across a wide range of wood & colours to suit any taste or environment c/w a 10year commercial warranty & 25 year domestic/residential warranty with 5S UV Coating and 0.5mm wear layer on a 5.2mm rigid core vinyl tile
- [COMES WITH 1MM BUILT IN UNDERLAY] Quiet & Comfort: enhanced sound absorption and underfoot comfort backed with 1mm enhanced underlay, our SPC flooring can reduce noise on upper floors, in high footfall areas, giving serene environment. (STC:73dB)
- [CLICK SYSTEM INSTALL] Patented Uninlic technology for durability and ease of install by any professional or DIY'er with cut bevel edges in a range of rooms from kitchen to bathroom, to office & corridor - also works with underfloor heating systems up to a maximum temperature of 27C
- [100% WATERPROOF] Excellent waterproof properties meaning you dont have to worry about spills or stains like traditional wooden or laminate flooring, as well as the highest rating R10 slip resistance makes it ideal for wet environments such as bathroom & kitchen while maintaining safety and practicality
- [DURABLE & PRACTICAL WITH 0.5MM WEAR LAYER] Stain & slip resistance, built for the family with anti-microbial properties & formaldehyde free keeping flooring spotless and making cleaning up a breeze with **10X protection** against damages such as scratches from pets, heavy footfall, drops & even cigarette burns (fire rating of B1)

If you're looking for an easily installed wood flooring alternative then look no further, long, plank-like body to imitate authentic wood, these elegant tiles offer the look of real wood minus the upkeep required of the real thing. A super-simple click system is on hand for quick and easy installation whilst make these vinyl tiles ideal for high-traffic areas such as kitchens and bathrooms. Available in five colour variants, these elegant vinyl tiles are incredibly versatile and can complement almost any interior design style.

Installation Guidance

Technical Parameters

Individual Plank Size 1100x184x5.2mm (5 per box ie. 1 sqm)

Use Area Classification ISO 10874 / EN 68523 Domestic Heavy Use

34 Very Heavy Commercial Use

43 Light Industrial UsePeeling strength of layers BS EN 431Pass 0.5MM WEAR LAYERShear forces of layers BS EN

432GoodResidual indentation after static load BS EN 433Mean value 0.01mmDimensional stability BS EN 434shrinkage

<0.02%;

curling 0.07 mmFlexibility-20mm mandrel BS EN 435No DamageResistance to chemicals BS EN 423Class 0Bearing to castor

chair BS EN 425No disturbance, no delaminationColour fastness to light ISO 105 B026Wear resistance BS EN 660TToxic

Product-Content Safety EN71-3 REACH SVHCNon Detected / CompliesResistance to fire ASTM E84-03NFPA Class B / Euro Class

B1Slip resistance DIN 51130R 10 non SlipFormaldehyde content test EN 717-1None Detected

Note - boards should be stored flat on pallet and opened in the installation room 24 hours prior to installation and allowed to climatise to the environment BEFORE install. If in direct sunlight ie. patio/glazed doors and areas, a 10mm expansion gap all around is needed.