[REGISTERED OFFICE ONLY]
The Levels
Capital Business Park
Cardiff
CF3 2PX
02920 099 098
sales@thisiswholesale.co.uk | https://www.thisiswholesale.co.uk/

UPVC Window Anthracite Grey - Double 1190mm w x 1040mm h (RAL7016) Left or Right Opening 2P

£212.40



Product Description

UPVC Window Anthracite Grey on White - Double 1190mm (RAL7016) 1190mm w x 1040mm h - Left or Right Opening Casement Window

Range of Stock Standard Sizes - Same Day Dispatch Range of Stock Standard Sizes - (*Single 610mm w x 820mm h (top hung), 610mm w x 1040mm h (side hung), Double: 1190mm w x 1040mm h, Triple: 1770mm w x 1040mm h)*

[ANTHRACITE GREY ON WHITE] RAL 7016 anthracite grey exterior with white interior 70mm Internally Beaded uPVC Profile: Slim, strong and insulating profiles combined with high quality glazing to create a thermally efficient window which is robust and easy to maintain. Foiled effect on Anthracite grey side, white internal face smooth finish.

[BOTH RIGHT-HAND & LEFT-HAND SIDE HUNG WINDOWS] Select opening type from options (as viewed from outside) supplied complete with 2-keys & high security lockable aluminium handle (white handle)

[28MM ARGON-FILLED LOW E INSULATED GLASS] A-rated1.4 W/mK Thermally efficient. Silver spaces. Clear coat Glass is Toughened to EN12150 for extra strength & security. Glass pre-fitted into frame for transport. Ease of install with side window straps or remove uPVC internal beading to drill through - Complies with 2022 Building Regulations regarding thermal performance Part L replacement & extensions

[TRICKLE VENTILATION FOR REDUCED CONDENSATION - BUILDING REGS PART F] Supplied with colour coded, openable trickle vents rated at 4000mm^2 both Internally & externally on the opening pane for passive air-flow in line with building regs Approved Document F. Internal weep wholes as standard to assist rain-water / drainage egress (note - trickle vent holes are routed, but trickle vents require installation with 2 screws)

[STANDARD STOCK SIZE 1190MM W X 1040MM H] Popular sizes in both Anthracite Grey or White **from stock for same day dispatch f**or a range of domestic window projects & applications. Generally advised to leave a 10mm tolerance in brickwork/aperture for ease of installation. NOTE - optional listed dimensions are window frame ONLY. IF select optional uPVC window cill - add 30mm to the overall height ie. 1040mm frame + 30mm cil = 1070mm total height

Optional uPVC window cil is cut slightly longer than the width of the window allowing you to cut in during installation. Supplied complete with 1 x pair of end-caps (loose) - can be glued or clipped in after install.

Frame ColourAnthracite Grey on White (Grey External / White Internal)Frame Depth70 mmFrame Height1040 mm inc. cil (1010mm without Sill)
Frame Type70mm uPVC CasementFrame Width1190mmGlazing Type28mm Double Glazed Argon Filled - Toughened EN12150HandedSide Hung (Select L or R - as viewed from outside)Insulation Type36mm Argon-Filled Insulating GlassManufacturer Guarantee10 Year Manufacturer's Guarantee (T&Cs Apply)Profile Type70mm Internally Beaded uPVC ProfileTransparencyClear (Soft Coat)U-Value1.4 W/mKVentilation TypeTrickle Ventilation 4000mmFixing MethodFrame Fix or Straps (select from Add ons)Cil Type / Size150mm (optional - select from Add ons)