


**UPVC Window White- Triple 1770mm w x  
1040mm h (RAL9010) Left or Right Opening  
3P Casement Window****£426.00****Product Description**

UPVC Window White- Triple 1770mm w x 1040mm h (RAL9010) Left or Right Opening 3P Casement Window

**Range of Stock Standard Sizes - Same Day Dispatch Range of Stock Standard Sizes - (Single 610mm w x 820mm h (top hung), 610mm w x 1040mm h (side hung), Double: 1190mm w x 1040mm h, Triple: 1770mm w x 1040mm h)**

[PURE WHITE RAL9010] Interior & Exterior 70mm Internally Beaded uPVC Profile: Slim, strong and insulating profiles combined with high quality glazing to create a thermally efficient window which is robust and easy to maintain. Foiled effect on Anthracite grey side, white internal face smooth finish.

[BOTH RIGHT-HAND & LEFT-HAND SIDE HUNG WINDOWS] Select opening type from options (as viewed from outside) supplied complete with 2-keys & high security lockable aluminium handle (white handle)

[28MM ARGON-FILLED LOW E INSULATED GLASS] A-rated 1.4 W/mK Thermally efficient. Silver spaces. Clear coat Glass is Toughened to EN12150 for extra strength & security. Glass pre-fitted into frame for transport. Ease of install with side window straps or remove uPVC internal beading to drill through - Complies with 2022 Building Regulations regarding thermal performance Part L replacement & extensions

[TRICKLE VENTILATION FOR REDUCED CONDENSATION - BUILDING REGS PART F] Supplied with colour coded, openable trickle vents rated at 4000mm<sup>2</sup> both Internally & externally on the opening pane for

passive air-flow in line with building regs Approved Document F. Internal weep wholes as standard to assist rain-water / drainage egress (note - trickle vent holes are routed, but trickle vents require installation with 2 screws)

[STANDARD STOCK SIZE 1770MM W X 1040MM H] Popular sizes in both Anthracite Grey or White **from stock for same day dispatch** for a range of domestic window projects & applications. Generally advised to leave a 10mm tolerance in brickwork/aperture for ease of installation. NOTE - optional listed dimensions are window frame ONLY. IF select optional uPVC window cill - add 30mm to the overall height ie. 1040mm frame + 30mm cil = 1070mm total height

*Optional uPVC window cil is cut slightly longer than the width of the window allowing you to cut in during installation. Supplied complete with 1 x pair of end-caps (loose) - can be glued or clipped in after install.*

Frame Colour Pure White RAL9100 (External & Internal) Frame Depth 70 mm Frame Height 1040 mm inc. cil (1010mm without Sill)

Frame Type 70mm uPVC Casement Frame Width 1770mm Glazing Type 28mm Double Glazed Argon Filled - Toughened EN12150 Handed Side Hung (Select L or R - as viewed from outside) Insulation Type 36mm Argon-Filled Insulating Glass Manufacturer Guarantee 10 Year Manufacturer's Guarantee (T&Cs Apply) Profile Type 70mm Internally Beaded uPVC Profile Transparency Clear (Soft Coat) U-Value 1.4 W/mK Ventilation Type 2 x Trickle Ventilation 4000mm Fixing Method Frame Fix or Straps (select from Add ons) Cil Type / Size 150mm (optional - select from Add ons)