



UPVC Window White- Triple 1770mm w x 1040mm h (RAL9010) Left or Right Opening 3P Casement Window**£426.00****2 X
Opening
Panels****1770mm w x 1040mm h**

UPVC Window White- Triple 1770mm w x 1040mm h (RAL9010) Left or Right Opening 3P Casement Window

Range of Stock Standard Sizes - Same Day Dispatch Range of Stock Standard Sizes - (Single 610mm w x 820mm h (top hung), 610mm w x 1040mm h (side hung), Double: 1190mm w x 1040mm h, Triple: 1770mm w x 1040mm h)

[PURE WHITE RAL9010] Interior & Exterior 70mm Internally Beaded uPVC Profile: Slim, strong and insulating profiles combined with high quality glazing to create a thermally efficient window which is robust and easy to maintain. Foiled effect on Anthracite grey side, white internal face smooth finish.

[BOTH RIGHT-HAND & LEFT-HAND SIDE HUNG WINDOWS] Select opening type from options (as viewed from outside) supplied complete with 2-keys & high security lockable aluminium handle (white handle)

[28MM ARGON-FILLED LOW E INSULATED GLASS] A-rated 1.4 W/m²K Thermally efficient. Silver spaces. Clear coat Glass is Toughened to EN12150 for extra strength & security. Glass pre-fitted into frame for transport. Ease of install with side window straps or remove uPVC internal beading to drill through - Complies with 2022 Building Regulations regarding thermal performance Part L replacement & extensions[TRICKLE VENTILATION FOR REDUCED CONDENSATION - BUILDING REGS PART F] Supplied with colour coded, openable trickle vents rated at 4000mm² both Internally & externally on the opening pane for passive air-flow in line with building regs Approved Document F. Internal weep wholes as standard to assist rain-water / drainage egress (note - trickle vent holes are routed, but trickle vents require installation with 2 screws)[STANDARD STOCK SIZE 1770MM W X 1040MM H] Popular sizes in both Anthracite Grey or White **from stock for same day dispatch** for a range of domestic window projects & applications. Generally advised to leave a 10mm tolerance in brickwork/aperture for ease of installation. NOTE - optional listed dimensions are window frame ONLY. IF select optional uPVC window cill - add 30mm to the overall height ie. 1040mm frame + 30mm cil = 1070mm total height*Optional uPVC window cil is cut slightly longer than the width of the window allowing you to cut in during installation. Supplied complete with 1 x pair of end-caps (loose) - can be glued or clipped in after install.*

Frame Colour	Pure White RAL9100 (External& Internal)	text_phone 02920 099 098
Frame Depth	70 mm	sales@thisiswholesale.co.uk https://www.thisiswholesale.co.uk/
Frame Height	1040 mm inc. cil (1010mm without Sill)	
Frame Type	70mm uPVC Casement	
Frame Width	1770mm	
Glazing Type	28mm Double Glazed Argon Filled - Toughened	
Handed	EN12150	
Insulation Type	Side Hung (Select L or R - as viewed from outside)	
Manufacturer Guarantee	36mm Argon-Filled Insulating Glass	
Profile Type	10 Year Manufacturer's Guarantee (T&Cs Apply)	
Transparency	70mm Internally Beaded uPVC Profile	
U-Value	Clear (Soft Coat)	
Ventilation Type	1.4 W/m ² K	
Fixing Method	2 x Trickle Ventilation 4000mm	
Cil Type / Size	Frame Fix or Straps (select from Add ons)	
	150mm (optional - select from Add ons)	