[REGISTERED OFFICE ONLY]
The Levels
Capital Business Park
Cardiff
CF3 2PX
02920 099 098
sales@thisiswholesale.co.uk | https://www.thisiswholesale.co.uk/

# Combination Code Keypad Lock - Steel Security Personnel Pedestrian Door for Keyless Entry - Industrial Grade Exterior Outdoor Security Door for Garage, Warehouse, Shed, Industrial Unit, Lockup, Shed, Shipping Container, Farm Barns

**£357.00**



## Product Description

Looking for upgraded Ultra High Security / heavy Duty Steel doors with 9 Point / Multi point Locking?

**Note - combination code keypad lock supplied loose and requires drilling.** DOWNLOAD COMBINATION CODE HANDLE LOCK INSTALLATION INSTRUCTIONS

Convenient 14-Digit Keypad for Multiple Access Codes- 12-digit keypad. This allows you to set multiple access codes. You can give codes to family members, friends, or service providers. It removes the need to share physical keys. The keypad is easy to use and program. You can change the codes whenever you want. This feature offers flexibility and convenience. It is intended for properties that have frequent visitors. Our keypad is user-friendly. So you can input the code quickly and unlock the door easily.

UNIVERSALLY HINGED LEFT OR RIGHT. SIMPLY ROTATE THE DOOR 180 TO HINGE ON THE OPPOSITE SIDE. SIMPLY SELECT OPEN IN OUR OUT. HINGED SIDE YOU CAN SELECT AT THE POINT OF INSTALLATION DEPENDING ON THE ORIENTATION OF THE INSTALL.

**Can I use these doors as a fire exit?** Our lockable external doors & lock sets are key lockable from the outside & thumb-turn release from the inside and thus a widely acceptable method of escape being defined as 'easily and immediately opened by any person in an emergency situation.' Some people assume that only doors with panic hardware/handles are acceptable - hence its advisable to check with your local building control officer BEFORE purchasing if you need clarification. Note - a fire exit door must open in the direction of passage/travel and thus in most cases open OUTWARDS.

Steel security door for outdoor/exterior use - industrial-grade personnel door is the ideal Security Door for Garage, Warehouse, Shed, Industrial Unit, Shipping Container, Farm Barn - can be primed & painted any colour yourself) complete with outer frame, & optional stainless steel door handle & lock with internal thumb turn & 3 sets of keys, single point locking mechanism). OPTIONAL POWDER COATED COLOURS (AT EXTRA COST)

- RAL 9003 WHITE (painted both sides in/out)
- RAL 7016 ANTHRACITE GREY (painted both sides in/out)
- RAL 9005 JET BLACK (painted both sides in/out)
- RAL 6007 JUNIPER GREEN (painted both sides in/out)

PLEASE NOTE - THIS IS ONE STANDARD SIZED 2035mm h x 840mm / 940mm / 1040mm wide - ITEM IS RECOMMENDED TO BE MEASURED, ORDERED AND INSTALLED BY A SUITABLE EXPERIENCED PROFESSIONAL AS WE DO NOT TAKE ANY LIABILITY FOR INCORRECT MEASUREMENTS. FULL TECHNICAL DRAWING WITH ALL DIMENSIONS IS BELOW & INSTALLATION INSTRUCTIONS.

FOR CUSTOM SIZES, PLEASE SEE OUR SIDE EXPANSION / EXTENSION PANELS THAT COME WITH WIND OUT LUGS ALLOWING EXTENSION OF BOTH SIDES AND HEADER SECTION FROM 10MM -100MM, THUS MAKING THIS DOOR SUITABLE FOR ALL SIZED APERTURES FROM 840MM T0 1140MM WIDTH AND 2035MM TO 2090MM H. FUTHER CUSTOM SIZES MADE ON REQUEST. CONTACT US FOR A QUOTE

Stock Door Size+ 35mm Side Panel+ 55mm Side Panel+ 35mm Header Panel+ 55mm Header Panel+ 75mm Header Panel840mm x 2035840mm - 890mm890mm - 940mm2035mm - 2070mm2070mm - 2090mm2090mm - 2105mm940mm x 2035940mm - 990mm990mm - 1040mm2035mm - 2070mm2070mm - 2090mm2090mm - 2105mm1040mm x 20351040mm - 1090mm1090mm - 1140mm2035mm - 2070mm2070mm - 2090mm2090mm - 2105mm

*Optional Add on 500mm x 300mm Louvre Vent or 400mm x 400mm / 220mm x 1500mm Vision Panels - SELF INSTALLATION / CUTTING REQUIRED (these are supplied with the door only for the customer to install) see instructions below for details. This add on is not pre-installed by ourselves and is only supplied with the door for the customer / installer to fit. Requires a competent and experienced installer, we accept no liability for mis-installation / mis-cutting or damage to product during installation. Frame powder coated both sides and will be sent the same colour as the door selected.* Note, 150mm clearance must be left around all 4 sides of the door.

**Weight: 840mm 46kg / 940mm 49kg / 1040mm 52kg**

DOWNLOAD PDF TECHNICAL DRAWING / DIMENSIONS

DOWNLOAD STEEL DOOR INSTALLATION INSTRUCTIONS / MANUAL

DOWNLOAD INSTRUCTIONS MANUAL FOR SIDE/HEADER EXPANSION INFIL PANELS

DOWNLOAD VISION GLASS PANEL / LOUVRE VENT INSTRUCTIONS

DOWNLOAD FIRE EXIT PUSH PAD/BAR + OUTSIDE ACCESS DEVICE INSTRUCTIONS

DOWNLOAD FIRE EXIT PUSH PAD/BAR + EXTERNAL BLANK INSTRUCTIONS

DOWNLOAD DOOR EXTERNAL BLANK / BLANKING PLATE INSTRUCTIONS

DOWNLOAD COMBINATION CODE HANDLE LOCK INSTALLATION INSTRUCTIONS

DOWNLOAD HIGH SECURITY MULTI-POINT LOCKING INC. PAS24 & FIRE RATED STEEL DOOR INSTALLATION INSTRUCTIONS

DOWNLOAD WC VACANT/ENGAGED CONVERSION KIT INSTALLATION INSTRUCTIONS

DOWNLOAD MAINTENANCE MANUAL

840mm / 940mm / 1040mm x 2035mm outer dimensions ie. to fit 840mm x 2035mm cut out (clear opening 750mm/850mm/950mm) - door frame thickness 75mm / door leaf thickness 45mm. Actual Door Size: 1943mm H x 750mm/850mm/950mm W - comes pre-hung in frame and fixing points located around the frame for easy install with the correct screws/fixings (not supplied) into brick, timber, steel or other building material. We recommend adding 5-10mm to the external size about for fitting which can be filled with foam / silicone. We would recommend adding a rain drip to any inward opening doors being installed externally helping to prevent water ingress. Frame features knock out weep holes at external footer.

**What is a vanity surround trim?**

When you install the door, you will inevitably get a small gap between say the block work or timber and the steel frame of the door on the reveal. This can be filled with silicone or expanding foam etc. The Vanity surround trim cover as a 3 pc kit of Angled steel (the same material + powder coated the same colour as the door) which is inserted between wall and door and fixed, using the return edge to essentially hide or make good this gap, thus removing the need for silicone etc. to tidy up this edge. This is an optional aesthetic part, supplied in 3 pcs (ie. 2 legs, 1 header) which you can custom cut to size to suit your installation (note - we recommend cutting the header piece to size first, then inserting the legs to get a clean edge. The legs should cut cut to size at ground level.

WE STOCK ALL: CONFIGURATIONS OF DOOR OPENING INWARDS OR OUTWARDS, AS VIEWED FROM OUTSIDE- Doors are universal and can be fitted with hinges either on the left or the right hand as viewed from outside by rotating the pre-latch mechanism,- SEE IMAGE FOR FURTHER DETAILS ON CONFIGURATIONS WHEN SELECTING YOUR VARIATION OF DOOR AS INCORRECT ORDERS/RETURNS MUST BE RETURNED AT BUYERS COST. IF IN DOUBT PLEASE ASK.

Door Frame Material1.5mm Galvanised SteelDoor Frame Thickness90mmDoor Leaf MaterialDouble skinned 0.7mm galvanised steelDoor Leaf Thickness45mmDoor Leaf Core50mm Mineral Wool Insulation
Actual Door Size1943mm x 750mm/850mm/950mmU Value1.6 w/mk (50mm Mineral Wool Insulation)Acoustic Value32dBaHinges4 Stainless steel hingesLock Cylinder Eurocylinder 70mm (35 - 35)

- *NOTE: due to manufacturing tolerances with regards to batch variation, we recommend ordering all coloured/powder coated doors for a project at the same time, from the same batch as we cannot be held responsible for any variation that occurs between batches.*
- *Must be installed by a competent persons, we are not able to train, teach any DIY enthusiast how to fit a door correctly. Whilst its not a difficult job, each individuals competency and skill set varies and thus professional knowledge is advised to fit this product correctly, safely and securely for normal operation.*
- *Note - door includes mechanical / moving parts such as lock mechanism, hinges, latches and as such requires regular maintenance and upkeep ion the form of regular lubrication/oil applying.*