

## SPC LVT Click Flooring - Vinyl Tile - Rigid Core Stone Polymer Composite Waterproof Click Tongue & Groove Luxury Vinyl Tile Flooring Grey Oak

**£23.94**



### SPC LVT Click Flooring - Vinyl Tile - Rigid Core 4.5mm Stone Polymer Composite Waterproof Click Tongue & Groove Luxury Vinyl Tile Flooring - Grey Oak

Get that sought-after authentic wood flooring look without the cost and upkeep required of the real thing thanks to SPC Luxury Vinyl Tiles; a click system is easy-to-install by any professional or DIY'er, a vinyl tile that faithfully replicates natural timber across a wide range domestic and commercial applications.

#### Sizing

**1230mm x 184mm per plank. 10 planks per box. Price is per sq metre. Sold by the square metre. Simply enter the number sq m of flooring you require in the quantity box (note - you may receive a box split as a full box of 10 is 2.26sq m). We recommend ordered an extra 10% coverage to cover wastage / cuts as delivery charges may apply for single sq meterage orders if you are short.**

#### Key Features

- [AUTHENTIC TEXTURED WOODGRAIN EFFECT] Matt finish across a wide range of wood & colours to suit any taste or environment c/w a 10year commercial warranty & 25 year domestic/residential warranty with 5S UV Coating and 0.5mm wear layer on a 4.5mm rigid core vinyl tile
- [CLICK SYSTEM INSTALL] Patented Uniclic technology for durability and ease of install by any professional or DIY'er with cut bevel edges in a range of rooms from kitchen to bathroom, to office & corridor - also works with underfloor heating systems up to a maximum temperature of 27°C
- [100% WATERPROOF] Excellent waterproof properties meaning you dont have to worry about spills or stains liek traditional wooden or laminate flooring, as well as the highest rating R10 slip resistance makes it ideal for wet

- environments such as bathroom & kitchen while maintaining safety and practicality
- [DURABLE & PRACTICAL] Stain & slip resistance, built for the family with anti-microbial properties & formaldehyde free keeping flooring spotless and making cleaning up a breeze with **10X protection** against damages such as scratches from pets, heavy footfall, drops & even cigarette burns (fire rating of B1)

If you're looking for an easily installed wood flooring alternative then look no further, long, plank-like body to imitate authentic wood, these elegant tiles offer the look of real wood minus the upkeep required of the real thing. A super-simple click system is on hand for quick and easy installation whilst make these vinyl tiles ideal for high-traffic areas such as kitchens and bathrooms. Available in five colour variants, these elegant vinyl tiles are incredibly versatile and can complement almost any interior design style.

	OriginWood SPC	Wood Floor	Laminate	Ceramic
Eco-friendly & Healthy	<b>YES</b>	YES	NO	NO
Enhanced performance & comfort available all spaces	<b>YES</b>	NO	NO	NO
Superbly durable without scratch or impact damage	<b>YES</b>	NO	YES	NO
100% waterproof	<b>YES</b>	NO	NO	YES
Dimensionally stable-will not expand or contract	<b>YES</b>	NO	YES	YES
Easy maintenance	<b>YES</b>	NO	NO	YES
Fast and easy to install with minimal floor prep	<b>YES</b>	NO	YES	NO
Install over existing floor surface	<b>YES</b>	NO	YES	NO

## Installation Guidance

## Technical Parameters

Individual Plank Size	1230mm x 184mm x 4.5mm
Use Area Classification ISO 10874 / EN 685	23 Domestic Heavy Use 34 Very Heavy Commercial Use 43 Light Industrial Use
Peeling strength of layers BS EN 431	Pass
Shear forces of layers BS EN 432	Good
Residual indentation after static load BS EN 433	Mean value 0.01mm
Dimensional stability BS EN 434	shrinkage <0.02%; curling €0.07 mm
Flexibility-20mm mandrel BS EN 435	No Damage
Resistance to chemicals BS EN 423	Class 0
Bearing to castor chair BS EN 425	No disturbance, no delamination
Colour fastness to light ISO 105 B02	≥6
Wear resistance BS EN 660	T
Toxic Product-Content Safety EN71-3 REACH SVHC	Non Detected / Complies
Resistance to fire ASTM E84-03	NFPA Class B / Euro Class B1
Slip resistance DIN 51130	R 10 non Slip
Formaldehyde content test EN 717-1	None Detected