

High Security Steel Security Door- 9 Point/Multi Point Locking - Ultra Heavy Duty External Industrial Grade Exterior Outdoor Security Door

£289.00



[Looking for Economy Steel External Doors? Click Here](#)

THIS IS WHOLESALE

**HIGH SECURITY
PERSONNEL
PEDESTRIAN
DOOR**





5 COLOURS & 3 SIZES UK STOCK AVAILABLE

- RAL 9003 WHITE
- RAL 7016 ANTHRACITE GREY
- RAL 9005 JET BLACK
- RAL 6007 JUNIPER GREEN
- RAL 5005 SIGNAL BLUE

Powder coated both in & out.


- 840mm W x 2035mm H
- 940mm W x 2035mm H
- 1040mm W x 2035mm H



4 x heavy duty hinges that offer extra security



Full set of stainless steel handle & lock



3 sets of keys, 9 points locking mechanism



Full weather seal to all 4 sides of the frame



The Levels,
Capital Business Park
Cardiff
CF3 2PX

text_phone 02920099098

sales@thisiswholesale.co.uk | <https://www.thisiswholesale.co.uk/>

SPECIFICATION SHEET

Door Frame Material	1.8mm Galvanised Steel
Door Frame Thickness	90mm
Door Leaf Material	Double skinned 0.8mm galvanised steel
Door Leaf Thickness	45mm
Clear Opening Size	1995mm H x 750mm/850mm/950mm W
U Value	1.6w/m²k (50mm Mineral Wool Insulation)
Acoustic Value	32dBa
Hinges	4 Stainless steel hinges
Weather Seal	Full weather seal to all 4 sides of the frame
Hole Cut Out Size	2035mm H x 840/940/1040mm W





The Levels,
Capital Business Park
Cardiff
CF3 2PX

text_phone 02920099098

sales@thisiswholesale.co.uk | <https://www.thisiswholesale.co.uk/>



Stainless steel
handle & two
locking system

Full key sets &
handles



INSTRUCTIONS

Steel Personnel Pedestrian Door to fit 840mm x 2035mm opening

THIS IS WHOLESALE .CO.UK


6pm CUT OFF TIME.
NEXT DAY DELIVERY.
10% TRADE DISCOUNT

1




Fit door in the hole hinged in the correct orientation (NOTE door is universal, i.e. can be fitted hinged on the left or right, just rotate 180° to so hinged on the opposite side).

2



Once door is square & firmly in position, using the pre-drilled tabs, mark fixing positions on the building lining frame & drill using suitable drill bit.


3



Optional: if ordered the extra add on vanity trim (not cover any caps/side), this can be fitted on the opposite side & secured with suitable adhesive /mastic.


Use anchor bolts or suitable frame fixings to secure in place (washers are advised). NOTE - due to various types of frame being installed into i.e. brick, metal, timber, we are unable to supply the door with fixings.

4




The lock mechanism latch can now be rotated to suit your configuration i.e. hinged left side or hinged right side using a screwdriver as shown.

5



Insert the lock mechanism cassette into the door & secure with the 2 x M5 screws as shown.

6



The lock barrel is fitted with with thumb turn from the inside / key insert to the outside. Handle & cover plate secured with screws as shown.

UNIVERSALLY HINGED LEFT OR RIGHT

Simply rotate the door 180° to hinge on the opposite side. Hinged side you can select at the point of installation depending on the orientation of the install.

BOTH IN & OUT POWDER COATING IN 5 DIFFERENT COLOURS

RAL 7016 Grey



RAL 9003 White





Ultra High Security / Heavy Duty Steel security door (9 point multi point Locking) for outdoor/exterior use - industrial-grade personnel door is the ideal Security Door for Garage, Warehouse, Shed, Industrial Unit, Shipping Container, Farm Barn - can be primed & painted any colour yourself) complete with outer frame, & stainless steel door handle & lock with internal thumb turn & 3 sets of keys, 9 point multi point locking mechanism). OPTIONAL POWDER COATED COLOURS (AT EXTRA COST)

- RAL 9003 WHITE (painted both sides in/out)
- RAL 7016 ANTHRACITE GREY (painted both sides in/out)
- RAL 9005 JET BLACK (painted both sides in/out)
- RAL 6007 JUNIPER GREEN (painted both sides in/out)
- RAL 5005 SIGNAL BLUE (painted both sides in/out)

PLEASE NOTE - THIS IS ONE STANDARD SIZED 2035mm h x 840mm - WE WHOLESALE STANDARD DOORS AND DO NOT MAKE THEM TO ORDER/CUSTOM SIZE. ITEM IS RECOMMENDED TO BE MEASURED, ORDERED AND INSTALLED BY A SUITABLE EXPERIENCED PROFESSIONAL AS WE DO NOT TAKE ANY LIABILITY FOR INCORRECT MEASUREMENTS. FULL TECHNICAL DRAWING WITH ALL DIMENSIONS IS BELOW & INSTALLATION INSTRUCTIONS.

Optional Add on 500mm x 300mm Louvre Vent or 400mm x 400mm / 220mm x 1500mm Vision Panels - SELF INSTALLATION / CUTTING REQUIRED (these are supplied with the door only for the customer to install) see instructions below for details. This add on is not pre-installed by ourselves and is only supplied with the door for the customer / installer to fit. Requires a competent and experienced installer, we accept no liability for mis-installation / mis-cutting or damage to product during installation. Frame powder coated both sides and will be sent the same colour as the door selected. Note, 150mm clearance must be left around all 4 sides of the door.

[DOWNLOAD PDF TECHNICAL DRAWING / DIMENSIONS](#)[DOWNLOAD INSTALLATION INSTRUCTIONS / MANUAL](#)

840mm x 2035mm outer dimensions ie. to fit 840mm x 2035mm cut out (clear opening 750mm) - door frame thickness 90mm / door leaf thickness 45mm. Actual Door Size: 1995mm H x 800mm W - comes pre-hung in frame and fixing points located around the frame for easy install with the correct screws/fixings (not supplied) into brick, timber, steel or other building material. We recommend adding 5-10mm to the external size about for fitting which can be filled with foam / silicone. We would recommend adding a rain drip to any inward opening doors being installed externally helping to prevent water ingress.

Exterior frame side comes with pre-fitted anti-jemmy trim/lip to face the installation taking overall dimensions to 880mm. If you want to recess the entire door including this frame section, you would need a sub frame internally in your aperture to suite 840 x 2035mm for structural fixing.

Optional add on of an internal vanity trim surround measures 905mm x 2090mm. This is an aesthetic part to cover any gaps between the door frame and your structural opening, often saving the need for silicone/foam etc. This is optional from the list of add

WE STOCK ALL: CONFIGURATIONS OF DOOR OPENING INWARDS OR OUTWARDS, AS VIEWED FROM OUTSIDE- SEE IMAGE FOR FURTHER DETAILS ON CONFIGURATIONS WHEN SELECTING YOUR VARIATION OF DOOR AS INCORRECT ORDERS/RETURNS MUST BE RETURNED AT BUYERS COST. IF IN DOUBT PLEASE ASK.

Door Frame Material	<i>Upgraded 1.8mm Galvanised Steel</i>	
Door Frame Thickness	<i>90mm</i>	
Door Leaf Material	<i>Double skinned 0.8mm galvanised steel</i>	
Door Leaf Thickness	<i>45mm</i>	
Door Leaf Core	<i>Honeycomb core</i>	
Actual Door Size	<i>1995mm x 800mm</i>	
U Value		<i>2.6</i>
Acoustic Value	<i>32dBa</i>	
Hinges	<i>4 Stainless steel ball bearing hinges</i>	

Eurocylinder
Lock *90mm (45 -*
Cylinder*45)*

NOTE: due to manufacturing tolerances with regards to batch variation, we recommend ordering all coloured/powder coated doors for a project at the same time, from the same batch as we cannot be held responsible for any variation that occurs between batches.

Must be installed by a competent persons, we are not able to train, teach any DIY enthusiast how to fit a door correctly. Whilst its not a difficult job, each individuals competency and skill set varies and thus professional knowledge is advised to fit this product correctly, safely and securely for normal operation.

Note - door includes mechanical / moving parts such as lock mechanism, hinges, latches and as such requires regular maintenance and upkeep in the form of regular lubrication/oil applying.